



Material Safety Data Sheet

MSDS Code: EBO1701018-M103

POLYMER LITHIUM BATTERY

Date of Issue: Jan 18,2017

Page 1 of 6

1. Identification Of Substance

Product Details

Product Name: POLYMER LITHIUM BATTERY

Product Model: 502535

Manufacturer/Supplier By: EAST(SHENZHEN)TECHNOLOGY CO.,LTD
11F,Taibang Technology Building,Nanshan District,
Shenzhen City,China

Tel: +86- 755-86006961

Fax: +86- 755-86968868

2. Composition/Data On Components

COMPONENT	CAS #	% by wt.
Lithium Cobalt Oxide	12190-79-3	36.26%
Carbon	7440-44-0	17.45%
Aluminum	7429-90-5	4.56%
Copper	7440-50-8	8.72%
Polyvinylidene Fluoride	24937-79-9	1.35%
Separator	/	1.23%
Electrolyte	/	15.0%
Nickel Plate	7440-02-0	0.22%
Plastic Film	/	14.21%
Conduct Additvie	/	1.0%

3. Hazards Identification



Material Safety Data Sheet

MSDS Code: EBO1701018-M103

POLYMER LITHIUM BATTERY

Date of Issue: Jan 18,2017

Page 2 of 6



HEALTH	2
FIRE	2
REACTIVITY	0

Hazard description:

Harmful! Do not short circuit, recharge, puncture, incinerate, crush, immerse, force discharge or expose to temperatures above the declared operating temperature range of the product. Risk of fire or explosion.

Under normal conditions of use, the electrode materials and liquid electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact. Risk of exposure only in case of abuse (mechanical, thermal, electrical) which leads to the activation of safety valves and/or the rupture of the battery containers. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances.

4. First aid Measures

Eyes:	Irrigate thoroughly with water for at least 15 minutes. Obtain medical attention.
Skin:	Wash off skin thoroughly with water. Remove contaminated clothing and wash before reuse. In severe cases obtain medical attention.
Inhalation:	Remove from exposure, rest and keep warm. In severe cases obtain medical attention.
Ingestion:	Wash out mouth thoroughly with water and give plenty of water to drink. Obtain medical attention.
Further treatment:	All cases of eye contamination, persistent skin irritation and casualties who have swallowed this substance or been affected by breathing its vapours should be seen by a Doctor.

5. Fire Fighting Measures

Hazardous Combustion Products:	When burned, hazardous products of combustion including fume of carbon monoxide and carbon dioxide can occur.
Extinguishing Media:	Water, carbon dioxide, dry chemical or foam.
Basic Fire Fighting Procedures:	Wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

6. Accidental Release Measures

Accidental

If the battery breakage and electrolyte leakage, evacuate personnel until the smoke cleared.

Wipe with a cloth and placed in steel drums into the bag inside.



Material Safety Data Sheet

MSDS Code: EBO1701018-M103

POLYMER LITHIUM BATTERY

Date of Issue: Jan 18,2017

Page 3 of 6

If the battery is hot, away from the scene firstly, cool the battery, so that the steam dissipated. Adequate ventilation. Avoid skin or eye contact steam.

Waste treatment

The battery Should discharge completely, the waste batteries will be turned over in the relevant sector, and all waste must refer to the United Nations, national, local regulations for disposal. Reference to national or federal Environmental Protection Agency EPA.

7. Handling And Storage

Prohibit mechanical or electrical damage battery.

Stored in a dry, cool and ventilated environment, to avoid temperature changes or high temperature.

Keep away from heat, avoid prolonged sun exposure.

Against short circuit, overcharge, forced discharge, or in a fire.

Battery disassembly, crush, fire or high temperatures can cause fire or explosion, prohibit short-circuit or error operation.

8. Exposure Controls And Personal Protection

Respiratory protection: If the battery leaks, the need for full ventilation.

Hand Protection: Under normal use, do not.

Personal Protection: Under normal use, do not.

Other protection: Under normal use, do not.

If the battery leaks, must wear the following protection products.

	Respiratory protection	In all fire situations, use self-contained breathing apparatus.
	Hand protection	In the event of leakage wear gloves.
	Eye protection	Safety glasses are recommended during handling.



Material Safety Data Sheet

MSDS Code: EBO1701018-M103

POLYMER LITHIUM BATTERY

Date of Issue: Jan 18,2017

Page 4 of 6

	Other	In the event of leakage, wear chemical apron.
---	--------------	---

9. Physical And Chemical Properties

Nominal Voltage:	3.7V
Capacity:	400mAh
Watt-hour:	1.48WH
Appearance characters:	Silvery with odorless battery

10. Stability And Reactivity

Product is stable under conditions described in Section 7.

Hazardous reactions may occur under some specific conditions.

Conditions to avoid: When a battery cell is exposed to an external short-circuit, crushes, modification, high temperature above 100 degree C, it will be the cause of heat generation and ignition. Avoid to be exposed to direct sunlight and high humidity.

Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.

Hazardous decomposition products: Acrid or harmful gas is emitted during fire.

11. Toxicological Information

Primary irritant effect: None, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibrotic lung injury and membrane irritation.

Inhalation: Lung irritant.

Skin contact: Skin irritant

Eye contact: Eye irritant.

Ingestion: Tissue damage to throat and gastro-respiratory tract if swallowed.

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur.



Material Safety Data Sheet

MSDS Code: EBO1701018-M103

POLYMER LITHIUM BATTERY

Date of Issue: Jan 18,2017

Page 5 of 6

12. Ecological Information

Environmental Impact

Proper use and disposal of the battery will not harm the environment.

Dispose of the battery, away from water, rain and snow.

13. Disposal Considerations

Do not incinerate, or subject cells to temperatures in excess of 100°C. Such abuse can result in loss of seal, leakage, and/or cell explosion.

Waste disposal must be in accordance with the applicable regulations. Disposal of the lithium ion battery cells should be performed by permitted, professional disposal page: firms knowledgeable in state or local requirements of hazardous waste treatment and hazardous waste transportation. Incineration should never be performed by battery but users, eventually by trained professional in authorized facility with proper gas and fume treatment.

14. Transport Information

According to IATA DGR 58th edition for transportation, or the special provision 188 of IMDG, or «recommendations on the transport of dangerous goods model regulations» .

UN-Number: UN3480

Lithium ion batteries in compliance with Section II of PI965, Corrugated Box (Thickness>6mm)

Each cell is of a type proved to meet the Requirements of each test in the UN MANUAL PF TESTS AND CRITERIA, part III, sub-SECTION 38.3, Each package is labeled with lithium battery handling label

Each consignment is accompanied with a document with an indication that:

the package contains lithium ion cells;

the package must be handled with care, and that a flammability hazard exists if the package is damaged;

special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and a telephone number for additional information.

Transport fashion: By air, by sea, by rail, by highway.

15. Regulations

«Dangerous Goods Regulation»

«Recommendations on the Transport of Dangerous Goods Model Regulations»

«International Maritime Dangerous Goods»

«Technical Instructions for the Safe Transport of Dangerous Goods»

«Classification and code of dangerous goods»

OSHA Hazard Communication Standard Status

Toxic Substances Control Act (TSCA) Status



Material Safety Data Sheet

MSDS Code: EBO1701018-M103

POLYMER LITHIUM BATTERY

Date of Issue: Jan 18,2017

Page 6 of 6

SARA Title III

RCRA

In accordance with all Federal, State and Local laws

16. Other Information

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

